

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 November 2002 (28.11.2002)

PCT

(10) International Publication Number
WO 02/096032 A2

(51) International Patent Classification⁷: **H04L 12/28**

(21) International Application Number: **PCT/EP02/05761**

(22) International Filing Date: **24 May 2002 (24.05.2002)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
TO2001A000496 25 May 2001 (25.05.2001) IT

(71) Applicant (for all designated States except US): **TELECOM ITALIA LAB S.p.A. [IT/IT]; Via G. R. Romoli, 274, I-10148 Torino (IT).**

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GREGO, Giorgio [IT/IT]; Telecom Italia Lab S.p.A., Via G. R. Romoli, 274, I-10148 Torino (IT).**

(74) Agent: **RIEDERER VON PAAR, Anton; Boehmert & Boehmert, Postfach 26 64, 84010 Landshut (DE).**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to the identity of the inventor (Rule 4.17(i)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU,

[Continued on next page]

(54) Title: **MOBILE COMMUNICATION NETWORK**



(57) Abstract: A mobile communication network (N) comprises at least one base transceiver station (BTS) configured to communicate with mobile terminals (T) connected to a corresponding coverage cell. The possibility of communication, which is obtained by means of first communication channels (C), is integrated with the implementation of at least one second communication channel (C') of the Bluetooth[®] type. According to the arrangement, said at least one second Bluetooth communication channel (C') can permit the communication between said base transceiver station (BTS) and said mobile terminals (T) even if none of said first communication channels (C) is available. Preferential application is in the context of shopping centres, airports, railway stations, stadiums, bus stops, underground train stations, etc., and in general in situations characterised by high possible variations in the traffic level depending on time.



ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ARIPO patent (GH, GM,

KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designation US
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US
- of inventorship (Rule 4.17(iv)) for US only

Published:

- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Mobile Communication Network

DESCRIPTION

5

The invention relates to mobile communication networks and particularly refers to a mobile communication network according to the preamble of claim 1.

10

Mobile communication networks of the type specified above, currently called "cellular" networks, are well known in the art and have reached a very wide and capillary diffusion over the past years.

15

One of the most characterising aspects of these networks is that the maximum number of mobile terminals which can connect simultaneously to a certain base transceiver station is limited by technological factors such as, for example, the maximum number of frequencies, or codes, which can be used within a cell

without reuse and/or the risk of possible interference with neighbouring cells. In other words (regardless of the nature of said limitations, related to the techniques adopted for establishing communication between mobile terminals and base transceiver stations), there is a maximum number of available
5 "channels" for communication between the mobile terminals and the base transceiver station (or base transceiver stations) in whose pertaining area the mobile terminals are at that time: the word "channel" is deliberately used according to its widest and most generic meaning.

10 In practice, a mobile terminal attempting to connect to the network to make a call (or, symmetrically, a mobile terminal to which an attempt is made to direct the call) cannot communicate when all the channels are engaged.

It being understood that the network characteristics can be adapted to suit
15 traffic requirements (e.g. by employing smaller cells and/or cells with higher availability of channels in areas where traffic is most intense, e.g. in major urban areas), there are various application scenarios in which the traffic may present very significant variations in time.

20 For example, at places such as shopping centres, airports, railway stations, bus stops, underground train stations, etc., the traffic to be dealt with may present a typical wave or "peak" pattern. Take the example of an airport in which peaks of calls can more than reasonably be expected immediately after the arrival of single flights with more or less prolonged periods in which the traffic to be
25 dealt with is more modest.

An extreme case is that of stadiums or other sports and show venues and facilities. For example, a considerable mass of people (even tens of thousands, with their corresponding telephone traffic needs) may crowd a stadium for a
30 short period of time (e.g. for a few hours or a little longer) for an event. The

venue may then remain practically deserted for days, and even weeks, until the following event is organised.

5 Dimensioning and configuring a mobile communication network to satisfactorily deal with the needs of traffic peaks which occur for only two or three hours a week (and even less frequently) is anything but an efficient solution as regards the general network economy.

10 The object of the invention is to provide a solution capable of overcoming this problem.

15 According to the invention, this object is achieved thanks to a mobile communication network having the characteristics specifically reported in the annexed claims.

Particularly, the solution according to the invention is based on the application of the technology currently known as Bluetooth®.

20 The salient aspects of this communication technology are entirely known in the art, even as concerns the formation and management of the "piconet" and "scatternet" networks and the respective implemented profiles. With regards to this, useful reference can be made to the web site www.bluetooth.com. Further reference is made to "Specification of the Bluetooth System", Version 1.1, 22-02-2001, a publication comprising two volumes "Core" and "Profiles".

25 For technological background purposes, reference can also be made, for example, to paper WO-A-0 069 186 that describes the creation of a cellular radio communication system from a set of local radio piconet networks implementing Bluetooth technology.

This technology can be used to connect equipment at a maximum distance of 100 m, at a bit-rate that can reach 720 kbps for data and with the possibility of generating a maximum number of three simultaneous audio channels.

5 Up to eight simultaneous users can be managed by each master unit (including the master). Up to 256 units can be held in stand-by conditions, offering the terminals the possibility to communicate with the master unit according to the availability of resources (typically because the communication with one of the seven slave units which were previously connected to the master unit fails).

10

The related implementation costs are not excessive. Today, there are mobile telephone terminals that are either configured or set-up for using Bluetooth technology on local communication level.

15

Essentially, the solution according to the invention is based on the possibility of establishing a communication between each terminal and the respective base transceiver station of the mobile network (possibility based on the use of GSM, GPRS or UMTS channels) with an additional possibility of connection offered by a radio link implementing Bluetooth technology and exploiting the ISM 2.4

20

GHz bandwidth.

25

As mentioned, terminals either configured or set-up for communicating with Bluetooth technology already exist today. The solution according to the invention consists in integrating this availability - already available or implemented on mobile terminal level - with a symmetric availability of communication via Bluetooth technology for the cellular network base transceiver station (BTS).

30

The invention will now be described, by way of example only, with reference to the following drawings wherein:

- figure 1 shows a typical mobile communication network configuration according to the known art in the form of a functional block chart, and
- figure 2 illustrates the criteria that can be used to implement the invention in the context of a network of the type illustrated in figure 1.

The diagram in figure 1 illustrates the typical configuration of a mobile communication network of the cellular type comprising a series of terminals T (only one of which is illustrated in the drawings for evident reasons of clarity). Each mobile terminal T can be connected to the network, generally indicated by reference N, by means of a "channel" C, comprising a series of communication channels which are made available by the base transceiver station BTS.

The specific implementation criteria of the channel C may vary according to the technology adopted in the context of the network N. This occurs according to criteria that are well known in the art and, for this reason, do not need to be specifically described herein. This also considering that the solution according to the invention is transparent with respect to the specific implementation characteristics of the network N to which the solution according to the invention is associated.

Proceeding with the illustration of the network chart in figure 1, reference BSC indicates the set of functions which supervise radio resource management, while reference SGSN indicates the set of functions pertaining to mobility management, authentication, encrypting and routing, implemented in a coordinated manner with the HLR (Home Location Register), the VLR (Visitor Location Register) and the MSC (Mobile services Switching Center) modules.

References GGSN indicate the respective sets of resources that supervise

gateway, mobility management, routing and encapsulation functions. This all in relation, for example, with an external data network N' or with other PLMN type public networks, generally indicated with reference N".

5 As previously mentioned, the structural and operational characteristics of the elements described above are entirely known in the art and, consequently, do not require a detailed description herein, also because they are not relevant for understanding this invention.

10 The configuration characteristics of the communication lines/channels intended to permit the interactions between the various modules/functions considered above are also concerned. With reference to this, it is noted that in both of the charts in figures 1 and 2, said lines/channels are represented by two-directional arrows. Particularly, solid lines indicate the lines intended to transfer user data
15 and dotted lines indicate the lines intended to permit the transfer of signals.

The salient characteristics of the solution according to the invention are shown in figure 2. The same references that appear in figure 1 are used to indicate identical or equivalent components/functions.

20 Essentially, the solution according to the invention integrates the set of communication channels C provided for communication between the base transceiver station BTS and the mobile terminals T connected at the time to the base transceiver station BTS with an additional connection channel C' implementing Bluetooth technology; all this using, on the one side, a communication
25 module BT (a chip of the type known *per se*), which may be installed in each mobile terminal T, and on the other side a Bluetooth interface BTB associated to the base transceiver station BTS.

30 Essentially, a mobile terminal T equipped with a corresponding Bluetooth BT

module can connect to the access point of the network N defined by the base transceiver station BTS in either of the following ways:

- by using the set of channels C normally available in the context of the network N,
- by exploiting a Bluetooth communication channel C' (in general in the context of cell whose dimensions are smaller than the network cell defined by the set of channels C).

This offers the consequent possibility of deviating the traffic (and the respective bandwidth engagement) to the Bluetooth module BT contained in the mobile terminal T, permitting to establish a connection with the Bluetooth function interface BTB in the base transceiver station BTS.

This solution can be implemented in small environments (e.g. shopping centres, airports, railway stations, bus stops, underground train stations, etc.) where the maximum distance envisaged for Bluetooth connections (approximately 100 m circa) is certainly sufficient.

This solution can also be implemented for the voice and data signal, which can thus be sent to the USB port, making it possible to manage a total of 14 audio/data channels (3+11) for each device in this way.

It will be appreciated once again that the use of such a solution is entirely independent (i.e. "transparent") with respect to the specific characteristics of the network N, which may be GSM, GPRS or UMTS, it being understood that the system management equipment (e.g. the MSC module) must be configured to be "informed" of the existence - as concerns the available resources - also of the Bluetooth channels.

The solution according to the invention also exploits the possibility of local traffic management offered by Bluetooth logic. This is because the master unit (usually identified by the Bluetooth function interface BTB of the base transceiver station BTS) is capable of managing the traffic of eight units - i.e. eight terminals T - active at the same time holding up to 256 units in stand-by until a slot in the respective piconet is freed.

In this way - on main cellular network N level - the possibilities of local user management offered by the control logic already implemented in Bluetooth devices can be exploited automatically and stand-by management can be established. This possibility has not been envisaged for traditional cellular networks in which, if the system is saturated (i.e. if the set of channels C is entirely engaged), the possibility of communicating will be absolutely precluded to any new mobile terminal T attempting to connect to the network (either to make or receive a call).

The only requirement is that each mobile terminal T must be at a sufficiently short distance - i.e. within the range of 100 m which is typical for Bluetooth technology - from the base transceiver station BTS to possibly exploit the Bluetooth network potentialities.

Except for this requirement (which - it must be stressed - is not a significant limitation in the typical situations of use herein envisaged), each active user who is connected to the network N via the piconet Bluetooth, instead of via a channel C (e.g. because all available channels are engaged at the time), anyway has an average bit-rate (downstream) not lower than 90 kbps (720/8 with symmetric link) or approximately 54 kbps with symmetric link (433/8) at his/her disposal.

If required, the base transceiver station BTS can be configured to implement

two types of charge, or tariffing; specifically a first charge level (generally higher) for the use of the typical cellular network channels C (with their higher distance range) and a second charge level (generally lower) for the possible access to the network N via the Bluetooth piconet channels C', with possible constraints related to the need of being in, and maintaining, a position which is sufficiently close to the base transceiver station BTS (or, more correctly, to the Bluetooth function via interface BTB).

The solution according to the invention - also in correspondence with places characterised by traffic requirements appearing in waves or peaks (refer to the examples listed in the preamble of this description) - permits the configuration of a cellular network N so that it can satisfy "average" traffic needs. The word "average" can be referred to time and/or to the possible geographic distribution in the context of the cell or the cells.

Each base transceiver station BTS in the network thus configured is integrated with a corresponding Bluetooth interface BTB which is capable of expanding the potentialities of communication (in the context of the corresponding Bluetooth piconet) to deal with traffic peaks deriving from users which can be located near the base transceiver station BTS, within the range of the respective Bluetooth piconet. This result is obtained by integrating the channels C of the cellular network N with the "auxiliary" channels C' of the Bluetooth piconet.

Additionally, the intrinsic flexibility of operation offered by the Bluetooth technology can be exploited, specifically as regards the possibility of implementing stand-by management, avoiding the need to absolutely reject the possibility of communication to a mobile terminal, even if all the channels C and C' are engaged at the time, offering the channels C' to the stand-by users as they are progressively unengaged by other users who have ended the communication.

It will also be appreciated that in the solution herein described, several Bluetooth interfaces BTB or functions can be installed in each base transceiver station BTS, to originate a so-called scatternet for each base transceiver station BTS. This possibility additionally increases the degree of flexibility of the system operation.

Naturally, numerous changes can be implemented to the construction and embodiments of the invention herein envisaged without departing from the scope of the present invention, as defined by the following claims.

CLAIMS

1. Mobile communication network (N) comprising at least one base trans-
5 ceiver station (BTS) configured to communicate with mobile terminals (T)
connected to a corresponding coverage cell via first communication
channels (C) which can be selectively activated, characterised in that said
base transceiver station (BTS) is associated to at least one Bluetooth®
communication unit (BTB) which can communicate with said mobile
10 terminals (T) via at least one second communication channel (C') of the
Bluetooth type; according to the arrangement, said at least one second
Bluetooth (BTB) communication channel (C') can permit the communica-
tions between said base transceiver station (BTS) and said mobile termi-
nals (T) even if none of said first communication channels (C) are avail-
15 able.
2. Communication network according to claim 1, characterised in that said
Bluetooth communication unit (BTB) establishes the communication with
said mobile terminals (T) in the context of a respective Bluetooth cell, said
20 respective Bluetooth cell being smaller in dimensions with respect to said
coverage cell.
3. Communication network according to claim 1 or claim 2, characterised
in that said Bluetooth communication unit (BTB) is configured to keep said
25 mobile terminals (T) in stand-by conditions for communicating with said
base transceiver station (BTS) via at least one second Bluetooth communi-
cation channel (C').
4. Communication network according to any of the previous claims, charac-
30 terised in that said base transceiver station (BTS) is configured to activate

a double charge mechanism for the communication established between said base transceiver station (BTS) and said mobile terminals (T), with a first charge level which is used when the communication between said base transceiver station (BTS) and the respective mobile terminal (T) is established by means of one of said first communication channels (C), and a second charge level which is used when the communication between said base transceiver station (BTS) and the respective mobile terminal (T) is established by means of at least one of the second Bluetooth communication channels (C').

5. Communication network according to any of the previous claims, characterised in that said base transceiver station (BTS) is associated with a series of Bluetooth communication units (BTB), said series of Bluetooth communication units being used to establish a corresponding scatternet for at least one base transceiver station (BTS).

FIG. 1





FIG. 2



THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 November 2002 (28.11.2002)

PCT

(10) International Publication Number
WO 02/096032 A3

(51) International Patent Classification⁷: **H04L 12/28**

(21) International Application Number: **PCT/EP02/05761**

(22) International Filing Date: **24 May 2002 (24.05.2002)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
TO2001A000496 25 May 2001 (25.05.2001) IT

(71) Applicant (for all designated States except US): **TELECOM ITALIA S.P.A.** [IT/IT]; Piazza degli Affari, 2, I-20123 Milano (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GREGO, Giorgio** [IT/IT]; Telecom Italia S.p.A., Via G. R. Romoli, 274, I-10148 Torino (IT).

(74) Agent: **RIEDERER VON PAAR, Anton**; Boehmert & Boehmert, Postfach 26 64, 84010 Landshut (DE).

(81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,**

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to the identity of the inventor (Rule 4.17(i)) for the following designations **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,**

[Continued on next page]

(54) Title: **MOBILE COMMUNICATION NETWORK**



(57) Abstract: A mobile communication network (N) comprises at least one base transceiver station (BTS) configured to communicate with mobile terminals (T) connected to a corresponding coverage cell. The possibility of communication, which is obtained by means of first communication channels (C), is integrated with the implementation of at least one second communication channel (C') of the Bluetooth[®] type. According to the arrangement, said at least one second Bluetooth communication channel (C') can permit the communication between said base transceiver station (BTS) and said mobile terminals (T) even if none of said first communication channels (C) is available. Preferential application is in the context of shopping centres, airports, railway stations, stadiums, bus stops, underground train stations, etc., and in general in situations characterised by high possible variations in the traffic level depending on time.

WO 02/096032 A3



- TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*
- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*
 - *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designation US*
 - *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US*
 - *of inventorship (Rule 4.17(iv)) for US only*
- Published:**
- *with international search report*
- (88) Date of publication of the international search report:**
16 October 2003
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 02/05761

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 42785 A (DEUTSCHE TELEKOM MOBILNET GMBH) 13 November 1997 (1997-11-13) page 2, line 16 -page 5, last line	1-4
A	WO 00 69186 A (TELEFONAKTIEBOLAGET LM ERICSSON) 16 November 2000 (2000-11-16) cited in the application	
A	WO 92 12579 A (TELENOKIA OY) 23 July 1992 (1992-07-23)	
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

12 March 2003

Date of mailing of the international search report

19/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Behringer, L.V.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/05761

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	NOERPEL A R ET AL: "SUPPORTING PACS ON A GSM MSC" IEEE COMMUNICATIONS MAGAZINE, IEEE SERVICE CENTER, PISCATAWAY, N.J, US, vol. 34, no. 9, 1 September 1996 (1996-09-01), pages 114-123, XP000627244 ISSN: 0163-6804 page 115, left-hand column, line 23 -right-hand column, line 19	1,3
A	HAARTSEN J: "BLUETOOTH - THE UNIVERSAL RADIO INTERFACE FOR AD HOC, WIRELESS CONNECTIVITY" ON - ERICSSON REVIEW, ERICSSON. STOCKHOLM, SE, no. 3, 1998, pages 110-117, XP000783249 ISSN: 0014-0171 page 116, left-hand column, line 1 -page 117, left-hand column, line 50; figure 9	5
X,P	EP 1 207 708 A (TELEFONAKTIEBOLAGET LM ERICSSON) 22 May 2002 (2002-05-22) column 4, line 46 -column 8, line 13	1-3

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 02/05761

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9742785	A	13-11-1997	DE 19617441 C1	18-12-1997
			AU 2887397 A	26-11-1997
			CZ 9803505 A3	17-02-1999
			WO 9742785 A1	13-11-1997
			EP 0896782 A1	17-02-1999
			PL 329646 A1	12-04-1999
WO 0069186	A	16-11-2000	SE 514264 C2	29-01-2001
			AU 3994200 A	21-11-2000
			CN 1360795 T	24-07-2002
			EP 1175793 A1	30-01-2002
			JP 2002544727 T	24-12-2002
			WO 0069186 A1	16-11-2000
			SE 9901673 A	08-11-2000
WO 9212579	A	23-07-1992	FI 910114 A	10-07-1992
			AT 139072 T	15-06-1996
			AU 654166 B2	27-10-1994
			AU 9113191 A	17-08-1992
			DE 69211330 D1	11-07-1996
			DE 69211330 T2	06-02-1997
			EP 0566603 A1	27-10-1993
			WO 9212579 A1	23-07-1992
			JP 2871093 B2	17-03-1999
			JP 6507278 T	11-08-1994
			NO 932318 A	09-07-1993
EP 1207708	A	22-05-2002	EP 1207708 A1	22-05-2002

Form PCT/ISA/210 (patent family annex) (July 1992)

THIS PAGE BLANK (USPTO)